

# PremiumColour ASLAN C 118 Soft

## The opaque polymeric colour film for long-term applications

The PremiumColour ASLAN C 118 Soft is an opaque polymeric film available in 36 brilliant and two matt colours to create high-quality letterings and brand-name plots. It is perfectly suitable for long-term decorations of vehicles, glass surfaces and signs.

The film is ideal for a computerised cutting of designs and lettering.

For any questions concerning special usage, for example with the use of translucent elastic cloth, please contact our technical advisory service:  
**+49 (0) 2204.708-80**

## Construction

face-film:	PVC (polymeric softeners)	
thickness:	~ 70 µm	
adhesive:	acrylic pressure adhesive	square quantity: ~ 20 g/m <sup>2</sup>
release liner:	silicone cardboard	square weight: ~ 140 g/m <sup>2</sup>

## Characteristics

adhesive strength: (ASTMD-903)	immediately after 1 week	~ 7.5 N/25 mm ~ 12 N/25 mm
dimensional stability:	applied onto aluminum after 48 hours stored at 70 °C (25 x 25 cm)	max. -0.45 %
chemical resistance:	In a preece test of 24 hours the applied film is resistant to most petroleum based oils, greases and aliphatic solvents, mild acids, alkaline and salts.	
light proofness:	DIN 53 388	non-fade grade: 6-8 Woll- Scale
combustibility:	Stuck on aluminum, the film is self-extinguishing.	
temperature:	application temperature: service temperature range:	min. 15°C -30 °C up to +80 °C
minimum durability:	7 years outdoors, with vertical exposure, in middle-European climate.	

### ASLAN, Schwarz GmbH & Co. KG

Oberauel 2 · 51491 Overath · Germany

**phone** +49 (0) 2204.708 80 · **fax** +49 (0) 2204.708 50

**e-mail** info@ASLAN-Schwarz.com



**www.ASLAN-Schwarz.com**

**ASLAN**®

EXPERTISE IN SELF-ADHESIVE FILMS

# PremiumColour ASLAN C 118 Soft

## Processing

<b>application:</b>	Application dry or wet. If applied wet, a possible whitening of the adhesive occurs but will fade away after a couple of days depending on the weather. For a wet application we recommend the transfer liquid ASLAN TL10. For the application of fonts etc. we recommend our ASLAN application tapes respectively the ASLAN TMO.
<b>gloss:</b>	There can be matt areas on the surface of the high glossy film near the core of the roll. These may be caused by the silicon cardboard flipside, but will disappear after a short period of time and don't influence the print results.
<b>storage life:</b>	Before application the foils can be stored for minimum 3 years from date of production. The film must be stored at room temperature (15-25 °C) and a relative humidity of the air of 50-60%. To avoid pressure points appearing on the roll surface, we recommend the rolls be stored either vertical standing or for this purpose designed 'hanging' racks.

State: 08|2015

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test the suitability of our products for the intended purpose.

The quality of our products is regularly examined, upgraded and developed. We take the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of our products in accordance with our latest knowledge.

### ASLAN, Schwarz GmbH & Co. KG

Oberauel 2 · 51491 Overath · Germany

**phone** +49 (0) 2204.708 80 · **fax** +49 (0) 2204.708 50

**e-mail** info@ASLAN-Schwarz.com



**www.ASLAN-Schwarz.com**

**ASLAN**®

EXPERTISE IN SELF-ADHESIVE FILMS