



# ALLJET DARK 803



SATINY  
FILM



160°C



PEEL : COLD



Flex Blade 45°  
Medium pressure



100µm



20 Sec

## SPECIFICATIONS


### APPLICATION

#### 1. Printing and cutting

- Print the image on positive
- Cut the design with a plotter and weed the excess material

#### 2. Heat pressing

- Transfer the image by hand.
- Position and heat press on a SEFA machine the image on the garment protected by a silicone paper at 160°C – 20 seconds – medium pressure.

**THICKNESS:**  White satiny film 100 microns  
*For use on inkjet and eco solvent printers.*

**CARRIER:** Paper



### APPLIES ON

This product is recommended for dark fabrics.  
Cotton ● Polyester ● Acrylic and similar fibres.

### CARE & MAINTENANCE

- Always respect the garment's instructions
- Allow 24 hours after application before washing
- Iron the backside only
- Printable media are very sensitive: always handle with care and preferably with gloves.
- Always store the roll in a plastic bag protected from dust.
- It is important always using official inks from the printer manufacturer.

### WASH

- Max 40°C
- Preferably inside out
- Do not bleach
- Tumble-dry unapproved
- Dry-cleaning unapproved

### STORE

- Up to 1 year
- In a dry room (15-25°C)
- Away from sunlight
- In vertical position

**Chemica**  
Heat transfers for textiles

NOTE: For best results, it is recommended to TEST prior to starting standard production