



NEWJET 804



MATT FILM



190°C



PEEL : HOT



Flex Blade 45°
Medium pressure



60 µm



20 Sec

SPECIFICATIONS


APPLICATION

1. Printing and cutting

- Print the image in reverse (mirror).
- Cut the excess material with scissors only.

2. Heat pressing

- Position and heat press the transfer on the garment protected by a silicone paper at 190°C – 20 seconds – medium pressure
- Peel off firmly and continuously the paper carrier immediately after heat pressing, starting from one edge.

THICKNESS:  Clear matt film 60 microns
For use on inkjet and eco solvent printers.

CARRIER: Paper



APPLIES ON

To be used only with light colored fabrics.
Cotton ● Polyester ● Acrylic and similar fibres.

CARE & MAINTENANCE

- Always respect the garment's instructions
- Allow 24 hours after application before washing
- Iron the backside only
- Printable media are very sensitive: always handle with care and preferably with gloves.
- Always store the roll in a plastic bag protected from dust.
- It is important always using official inks from the printer manufacturer.

WASH

- Max 40°C
- Preferably inside out
- Do not bleach
- Tumble-dry unapproved
- Dry-cleaning unapproved

STORE

- Up to 1 year
- In a dry room (15-25°C)
- Away from sunlight
- In vertical position

Chemica
Heat transfers for textiles

NOTE: For best results, it is recommended to TEST prior to starting standard production