

- INT 212**
- INT 234**
- INT 235**
- INT 333**
- INT 343**
- INT 435**
- INT 500**

**Description :** decorative films enhance clear glass with a wide range of designs and patterns. Add privacy and style to office partitions, ground level windows, doors and many other applications.

**For :** facades, office partitions, computer rooms, hospitals, floor level rooms, schools, workshops, decoration of devantures, etc...

**Application method :** internal surface with soapy water.

**Glass maintenance :** the film may be cleaned with soapy water, 30 days after the application. Any abrasive products that could scratch the film, are not recommended. Do not apply any stickers, or any other type of adhesives on the film.

**Durability :** 12 to 15 years for vertical application in Central Europe.

**Storage :** 2 years from the delivery date. This film has to be kept away from excessive humidity. It also has to be stored away from direct sunlight at a temperature under 38°C.

**Important factors :** the glass surface used must be entirely dirt free and any grease or other filth must be removed prior to installation. Gas may be given off from certain polycarbonate surfaces which are too new or of mediocre quality. This may be unsightly but does not lessen the adhesive qualities of the film. Users are recommended to carry out a trial beforehand to avoid bubbling issues.

<b>Material</b>	Polyester 36 microns
<b>Adhesive</b>	Acrylic polymer 13 gr/m <sup>2</sup>
<b>Release liner</b>	Siliconed polyester 23 microns
<b>Application</b>	Internal
<b>INT 212</b>	White stripes film Stripes of 13 mm x 6 mm of clear film
<b>INT 234</b>	Decreasing white stripes film Stripes from 26 to 1 mm
<b>INT 235</b>	Decreasing white stripes film Stripes from 290 to 127 mm
<b>INT 333</b>	Cocoon film
<b>INT 343</b>	White dots film Dots of 3 mm diameter
<b>INT 435</b>	Screened white stripes film Stripes of 43 mm
<b>INT 500</b>	Horizontal white lines film
<b>Thermal resistance</b>	from -20°C to 80°C
<b>Application temperature</b>	Minimum 5°C
<b>Dimensions</b>	60'' x 8,34' 60'' x 33,34' 60'' x 100'

Fire performance class

**M1**

Please make sure to match the correct specifications when applying your film. You may follow the glass compatibility guideline, especially concerning thermal stress.

Please note that Reflectiv does not guaranty the glass quality or the incorrect use of its films and claims the possibility of changing the production process or tints without previous notification.